




E.R.W. TUBING

Electric Resistance Welding Tubing


Shape	Commercial	Galvanized	Shape	Commercial	Galvanized
Rounds O.D. x wt	Mass kg/m	Mass kg/m	Squares mmxmmxmm	Mass kg/m	Mass kg/m
12.7 x 1.2	0.341	-	12.7x12.7x1.2	0.449	-
12.7 x 1.6	0.438	-	12.7x12.7x1.6	0.582	-
15.9 x 1.2	0.438	0.438	15.9x15.9x1.2	0.553	-
15.9 x 1.6	0.568	-	15.9x15.9x1.6	0.720	-
19.0 x 1.2	0.527	0.527	19.0x19.0x1.2	0.642	0.677
19.0 x 1.6	0.687	0.687	19.0x19.0x1.6	0.840	0.889
19.0 x 2.0	0.838	-	22.2x22.2x1.2	0.762	-
22.2 x 1.2	0.621	0.622	22.2x22.2x1.6	1.000	-
22.2 x 1.4	0.718	-	25.4x25.4x1.2	0.883	0.906
22.2 x 1.6	0.813	0.813	25.4x25.4x1.4	1.023	-
25.4 x 1.2	0.716	0.716	25.4x25.4x1.6	1.161	1.192
25.4 x 1.6	0.939	0.939	25.4x25.4x2.0	1.415	-
25.4 x 2.0	1.154	-	31.8x31.8x1.26	1.159	-
28.6 x 1.2	0.811	-	31.8x31.8x1.6	1.483	1.531
28.6 x 1.6	1.066	-	34.9x34.9x1.6	1.630	-
31.8 x 1.2	0.906	0.906	38.1x38.1x1.6	1.794	-
31.8 x 1.6	1.192	1.192	50.8x50.8x1.6	2.443	2.443
31.8 x 2.0	1.470	-	Electric Resistance Welding Tubing		
38.1 x 1.2	1.089	1.089	Shape	Commercial	Galvanised
38.1 x 1.6	1.440	-	Rectangles mmxmmxmm	Mass kg/m	Mass kg/m
38.1 x 2.0	1.780	-			
38.1 x 2.5	2.270	-	25.4x12.7x1.2	0.642	-
41.3 x 1.6	1.566	1.567	25.4x12.7x1.6	0.842	-
44.5 x 1.6	1.693	1.693	34.9x19.0x1.6	1.242	-
47.6 x 1.6	1.815	-	38.1x25.4x1.6	1.478	1.478
50.8 x 1.2	1.474	-	38.1x25.4x2.0	-	1.894
50.8 x 1.6	1.941	1.949	50.8x25.4x1.6	1.815	1.815
50.8 x 2.0	2.407	-	50.8x31.8x1.6	2.131	-
54.0 x 1.6	2.068	-	50.8x31.8x2.0	2.417	-
57.2 x 1.6	2.186	-	57.1x34.9x1.6	2.186	-
57.2 x 2.0	2.713	-	57.1x34.9x2.0	2.713	-
60.3 x 1.6	2.316	-	Electric Resistance Welding Tubing		
60.3 x 2.0	2.876	-	Shape	Commercial	Galvanised
63.5 x 1.6	2.442	-	Ovals mmxmmxmm	Mass kg/m	Mass kg/m
63.5 x 2.0	3.033	-			
76.2 x 1.6	2.940	-	31.0x16x1.6	0.939	-
76.2 x 2.0	3.655	-	51.0x16x1.6	1.464	-



Easy to cut, weld, drill, paint or powder coat



Suitable for a wide range of uses



Commercial tubing has a smooth finish - ideal for Chrome Plating.



Finish: Pre Galvanized commercial grade to G250 Z275 and G310 Z450. Surfaces are lightly oiled.
Standard lengths: ERW Sections are normally supplied in 6.100 metres. However special lengths may be negotiated. Other section sizes may be available.
Thickness tolerance: (+/- 8%) of specified wall thickness. Lengths supplied as -0mm + 50mm.
Some many uses include: Tent Poles, Coach Framing, Luggage & Shopping Trolleys, Outdoor Furniture, Safety Ladders, Fencing & Framing, Handrailing & Balustrading, Children's Play Equipment